Active Project (2016 - 2018)

# Designer Fluid for use in a Single Loop Variable Heat Rejection Thermal Control System, Phase II Project SBIR/STTR Programs | Space Technology Mission Directorate (STMD)

NASA

# ABSTRACT

The efficient thermal control of vehicles is essential to the success of every single NASA mission. All vehicles have very tight requirements for the thermal control systems while simultaneously placing incredibly stringent demands upon them. These demands are getting even more intense given the shift towards variable heat rejection, which is essential in missions reaching beyond the lower earth orbit. Specifically, the thermal control fluid must maintain excellent thermal properties for heat rejection under peak conditions while at the same time remain liquid at extremely low temperatures. Currently used fluids either do not meet the low temperature requirement (glycol/water mixture) or do not have thermal properties conducive to a compact, efficient system (Galden). Mainstream has identified several promising next generation thermal fluids using computation chemical techniques. Mainstream has already demonstrated in Phase I that these fluids are superior to incumbent fluids. In Phase II, Mainstream will perform more long term durability, compatibility and performance studies in a simulated test-loop representative of conditions encountered on NASA spacecraft.

#### **ANTICIPATED BENEFITS**

#### To NASA funded missions:

Potential NASA Commercial Applications: This program will result in a fluid or family of fluids providing a significant benefit to NASA in enabling efficient variable heat rejection thermal control systems. The fluids will be formulated at Mainstream complete with any necessary additive packages to ensure stability, materials compatibility and safety. The commercial market for these fluids within NASA is immense and includes essentially every spacecraft which would require a single phase thermal control loop.

## To the commercial space industry:


Potential Non-NASA Commercial Applications: In addition to an



#### **Table of Contents**

| Abstract 1                  |
|-----------------------------|
| Anticipated Benefits1       |
| Technology Maturity 1       |
| Management Team 1           |
| U.S. Work Locations and Key |
| Partners 2                  |
| Technology Areas 2          |
| Image Gallery 3             |
| Details for Technology 1 3  |

### **Technology Maturity**



#### **Management Team**

# **Program Executives:**

- Joseph Grant
- Laguduva Kubendran

## **Program Manager:**

Carlos Torrez

Continued on following page.

Active Project (2016 - 2018)

# Designer Fluid for use in a Single Loop Variable Heat Rejection Thermal Control System, Phase II Project

SBIR/STTR Programs | Space Technology Mission Directorate (STMD)




attractive market within NASA, these fluids will have far reaching effects in other commercial markets as well. These applications include freeze protection, process cooling, refrigeration coil defrosting and sub-ambient dehumidification.

# Management Team (cont.)

#### **Principal Investigator:**

• Ted Amundsen

#### U.S. WORK LOCATIONS AND KEY PARTNERS



# U.S. States With Work

# 🜟 Lead Center:

Johnson Space Center

## Other Organizations Performing Work:

Mainstream Engineering Corporation (Rockledge, FL)

#### **PROJECT LIBRARY**

#### **Presentations**

- Briefing Chart
  - (http://techport.nasa.gov:80/file/23420)

# **Technology Areas**

#### **Primary Technology Area:**

Thermal Management Systems (TA 14)

- □ Thermal Control Systems (TA 14.2)
  - ☐ Heat Transport (TA 14.2.2)

Active Project (2016 - 2018)

# Designer Fluid for use in a Single Loop Variable Heat Rejection Thermal Control System, Phase II Project SBIR/STTR Programs | Space Technology Mission Directorate (STMD)



# **IMAGE GALLERY**

| COMPOUND      | BOILING<br>POINT<br>(°C) | FLASH<br>POINT<br>("C) | FLAMMABILITY RATING | HEALTH | ји-90°С) | FIGURE<br>OF<br>MERIT | LAMINAR                                |                  |
|---------------|--------------------------|------------------------|---------------------|--------|----------|-----------------------|--|------------------|
|               |                          |                        |                     |        |          |                       | W <sub>1</sub> /<br>W <sub>Noses</sub> | k <sub>t</sub> / |
| GALDEN HT 170 | 170                      |                        | 0                   | 1      | 212      | 0.4                   | 5.03                                   | 0.81             |
| NOVEC 7200    | 76                       |                        | 1                   | 1      | 12       | 1                     | 1                                      | 1                |
| MEC-1         | 183                      | 59                     | 2                   | 0      | 31       | 0.91                  | 1.95                                   | 1.63             |
| MEC-2         | 172                      | 92                     | 1                   | 1      | 26       | 0.92                  | 1.83                                   | 1.56             |

Designer Fluid for use in a Single Loop Variable Heat Rejection Thermal Control System, Phase II

#### **DETAILS FOR TECHNOLOGY 1**

## **Technology Title**

Designer Fluid for use in a Single Loop Variable Heat Rejection Thermal Control System, Phase II

# **Potential Applications**

This program will result in a fluid or family of fluids providing a significant benefit to NASA in enabling efficient variable heat rejection thermal control systems. The fluids will be formulated at Mainstream complete with any necessary additive packages to ensure stability, materials compatibility and safety. The commercial market for these fluids within NASA is immense and includes essentially every spacecraft which would require a single phase thermal control loop.